

**TECHNICAL DATA
MULTI-TURN ELECTRICAL ACTUATORS
NON - RISING STEM - ON/OFF DUTY**


400 SERIES

Model	Tripping Torque		Output speed (1/min.)	Valve coupling ISO 5210	Max. Stem diameter output type B0 (mm)	Handw heel diameter (mm)	Max. Stem length output type B0 (mm)	Revolutions for full stroke (Nº of turns)	Weight (kg)
	Máx (N.m)	Min (N.m)							
400.001 402.001	15	9	22	F10	20	125	53	2-1.500 (Optional 2-15.000)	20,8
			28						
			44						
			56						
			88						
			112						
			175						
224									
22									
400.003 402.003	30	18	11	F10	20	125	53	2-1.500 (Optional 2-15.000)	20,8
			14						
			22						
			28						
			44						
			56						
			88						
			112						
			175						
224									
21,3									
21,6									
400.006 402.006	60	36	11	F10	20	125	53	2-1.500 (Optional 2-15.000)	21,3
			14						
			22						
			28						
			44						
			56						
			175						
			224						
22									
23,6									
24,5									
400.012 402.012	120	72	11	F14 (Optional F10)	30 (20)	200	71	2-1.500 (Optional 2-15.000)	21,3
			14						
			22						
			28						
			44						
			56						
			175						
224									
22									
33,7									
35,8									
400.025 402.025	250	150	22	F14	30	200	71	2-1.500 (Optional 2-15.000)	32,4
			28						
			44						
			56						
			175						
			224						
34									
34,8									
43,4									
44,2									

All speeds obtained with 50 Hz. supply. For 60 Hz. supply, multiply the output speeds by 6/5.
All actuators are standard non-self locking.

*In the table, 400 series actuators weights are indicated. The 402 series actuators weigths can be obtained by adding 7,6 Kgs. to the 400 series actuators weigths.

Subject to change without notice. Previous data sheets invalid with the issue of the latest data sheets.

VALVE CONTROL		Nº : E1400A001	Issued: 06.02
CENTRALAIR, S.A. All rights reserved.			