

**TECHNICAL DATA
MULTI-TURN ELECTRICAL ACTUATORS
RISING STEM - ON/OFF DUTY**


SERIES 401

Model	Tripping Torque		Output speed (1/min.)	Valve coupling Flange ISO 5210	Max. stem diameter Output type B0 (mm)	Handw heel diameter (mm)	Max. stem length output type B0 (mm)	Revolutions for full stroke (Nº of turns)	Weight (kg)
	Máx (N.m)	Min (N.m)							
401.050 403.050	500	300	2,75	F14	56	200	160	2-375 (Opcional 2-3.750)	51
			3,5						50,8
			5,5						
			7						
			11						
			14						
			22						
			44						
			56						
			88						
112									
401.100 403.100	1000	600	11	F16	75	200	250	2-375 (Opcional 2-3.750)	64,6
			14						65,3
			44						73,9
			56						74,7
401.200 403.200	2000	1200	5,5	F25	90	200	380	2-187 (Opcional 2-1.870)	95
			7						95,7
			22						104,3
			28						105,1

All speeds obtained with 50 Hz. supply. For 60 Hz. supply, multiply the output speeds by 6/5.
All actuators are standard non-self locking.

*In the table, 400 series actuators weights are indicated. The 402 series actuators weights can be obtained by adding 7,6 Kgs. to the 400 series actuators weights.

Subject to change without notice. Previous data sheets invalid with the issue of the latest data sheets.

	Nº : E1401B002	Issued: 06.02
CENTRALAIR, S.A. All rights reserved.		