

**SWITCHING AND SIGNALLING UNIT
OPTIONAL ELECTRICAL COMPONENTS**

**400 410
401 411
402 414
403 415** SERIES

Auxiliary signalling unit:

- AUX1: Auxiliary signalling microswitch 1.
- AUX2: Auxiliary signalling microswitch 2.
- AUX3: Auxiliary signalling microswitch 3.



Specifications:

- Version : Microswitch with silver contacts (gold contacts on request).
- Switch Type : 1 NA (SPDT).
- Actuation : Lever.
- Contacts : One fast acting.
- Contact Material : Silver.
- Temperature : - 20 + 125 °C
- Switching Capacity :

Silver contact	AC			DC		
	30V	125V	250V	30V	125V	250V
Resistance	4A	4A	4A	2A	0,6A	0,4A

- Mechanical lifetime : 3 x 10 .
- Electrical lifetime : 3 x 10.

Anti-condensation Heater:

The number of turns, valve stroke, is necessary for the correct sizing of this component.

- HT: Anti-condensation heater.
Avoids condensation by rising the temperature of the switching and signalling unit.

- Supply voltage : 220V AC.
24V DC.
- Power consumption : 5 - 7 W.



Subject to change without notice. Previous data sheets invalid with the issue of the latest data sheets.

VALVE
CONTROL



N° :

E1400A005

Issued:

06.02